Application No.: 10/666,924 Response Date: June 13, 2005

Reply to Office Action Dated April 14, 2005

REMARKS

In the Claims:

Claims 8-19 are currently pending.

CLAIMS REJECTED UNDER 35 U.S.C. § 103(a)

The Examiner has rejected Claims 8-19 under 35 U.S.C. § 103(a) as being unpatentable over Kovacs (DE 3335962) in view of Takada et al. (JP 61-39416). Applicants respectfully traverse this rejection.

Examiner contends that Kovacs proposes to use a four-cycle engine for a chain saw, Takada discloses a lubrication apparatus, and one of ordinary skill in the art would combine the engine lubrication of Takada with the tool of Kovacs. However, the Examiner has not identified any motivation in Kovacs or Takada for combining these references and then miniaturizing them; has not shown any evidence or suggestion that the miniaturization of Kovacs combined with Takada would result in an operable, handheld, portable power tool; and has not shown how the references could be combined without drastically altering what the references disclose.

Neither Kovacs nor Takada suggest their combination or miniaturization. The Examiner's purported reasoning that miniaturization was not done prior to Applicants' invention because of expense, and not technology, is not supported. There is no showing that the mere miniaturization of either the partial engine of Kovacs or the lubrication system of Takada will necessarily result in a properly working engine for use on a portable, handheld power tool. Without a showing that mere miniaturization would accomplish that which is taught in Claims 8-19 the Examiner's contention simply amounts to speculation. In re Fritch, 972 F.2d 1260, 1265-66 (Fed. Cir. 1992) (stating that the mere fact that the prior art may be modified in the manner suggested by the Examiner does not make the modification obvious to one skilled in the art unless the prior art suggested the desirability of the modification). There is no teaching as to how the partial four-cycle engine taught in Kovacs or Takada can be miniaturized to provide a reduction in weight and size in order to be used with a hand-held tool. To the contrary, the scientific community recognized that miniaturization alone would not

Application No.: 10/666,924 Response Date: June 13, 2005

Reply to Office Action Dated April 14, 2005

accomplish what Applicants invented. For example, the 1993 Popular Science article titled *The Little Engine That Could* (attached hereto as Ex. A) states that to characterize Ryobi's four-cycle engine as "just miniaturizing" is "an understatement of the cleverness of the Ryobi engine design." (Ex. A, p. 92). The Examiner's contention that simply miniaturizing the partial four-cycle engine of Kovacs and combining it with the lubrication apparatus of Takada would have been obvious to one skilled in the art is inapposite in view of the findings of this article. The Examiner has not provided a reference to indicate a teaching or motivation that combining Takada and Kovacs would be obvious to one skilled in the art. Further, there is nothing in either Kovacs or Takada that suggests miniaturization of the Takada lubrication system. Such a combination and the further miniaturization of that combination is mere speculation that is made with the benefit of hindsight only, which is improper. In re Fitch, 972 F.2d at 1266 (stating that it is impermissible to use the claimed invention as a template to piece together a teaching from the prior art so that the claimed invention is rendered obvious).

The Examiner also contends that one of ordinary skill in the art would be motivated to combine the lubrication system of Takada with the 4-cycle engine of Kovacs in order to obtain the advantages of Takada. On the contrary, Applicants submit that one of ordinary skill in the art would not be motivated to combine Kovacs and Takada because the combination would result in something that eliminates the required features of one or both of the references. Specifically, Kovacs discloses certain important engine features that are drastically different from those in Takada. For example, Kovacs requires that "the engine is built with an inlet and outlet *in the cylinder head*" (Kovacs, p. 2). Further, Kovacs requires two inlet openings (Kovacs, p. 2), the second being in the cylinder center (Kovacs, p. 2). By comparison, Takada requires that the inlet and outlet valves as well as the mechanism for operating the valves be "provided above the cylinder head" (Takada, p. 2). The structures of Kovacs and Takada do not appear to be compatible and any combination of the two would significantly alter the structure disclosed by each of those references. There can be no

¹ This article refers to Ryobi because the parent application was originally assigned to Ryobi. Ryobi has since transferred all of its rights to MTD.

Application No.: 10/666,924 Response Date: June 13, 2005

Reply to Office Action Dated April 14, 2005

motivation in a situation such as this. <u>In re Fitch</u>, 972 F.2d at 1265 n. 12 (stating that a proposed modification is inappropriate for an obviousness rejection if the modification would render the prior art reference inoperable for its intended purpose); <u>In re Gordon</u>, 733 F.2d 900, 902, 221 USPQ 1125, 1127 (Fed. Cir. 1984).

Further, there is no teaching in Takada as to how the disclosed lubrication system is capable of being adapted to be incorporated into different engines, let alone the partial engine disclosed in Kovacs. Without further teaching, it would not be obvious to one skilled in the art to combine the lubrication apparatus of Takada with the four-cycle engine of Kovacs. Therefore, Applicants submit that Claims 8-19 are patentable over the prior art, and that the present apparatus is not an obvious combination of Takada and Kovacs.

In view of the foregoing comments, Applicants respectfully submit that Claims 8-19 are patentable over Kovacs in view of Takada et al., and the claims are in a condition ready for allowance. In the event issues remain that the Examiner feels might be resolved by interview, he is respectfully requested to telephone applicant's attorney at (312) 321-4221.

Respectfully submitted.

Robert S. Mallin

Registration No. 35,596 Attorney for Applicant

BRINKS HOFER GILSON & LIONE P.O. BOX 10395 CHICAGO, ILLINOIS 60610

(312) 321-4200

U.S. AIR FORCE

THE WHAT'S NEW MAGAZINE

Popular Science

MARCH 1993 Founded in 1872/Vol. 242, No. 3

Secret Mach 6
spy plane

An eyewitness description, a secret Nevada test site, and a new look at advanced aeronautics paint a portrait of Aurora, America's newest secret reconnaissance aircraft. A Federation of American Scientists report also posits the existence of the plane, along with others flying in the Pentagon's "black world."

mentally friendly themes.

66 A house for all reasons

The architectural style may be classic Mediterranean villa, but the 1993 New American Home contains some of the most technologically advanced homebuilding products available today, complementing the home's energy-saving and environ-



74 The unbearable lightness of space travel

Prolonged weightlessness in near-zero gravity could endanger human health, as well as NASA's plans for long missions. The ill effects include musclewasting and heart shrinkage. Here's how researchers are studying the problems—and hope to solve them.

80 Minivans to the max

Volkswagen EuroVan, Mercury Villager, Nissan Quest, and Dodge Grand Caravan: One is the tallest, two are the widest, and one is the longest. We tell you which is which and which is the best.



90

The little engine that could

This one-cylinder four-cycle gas-powered engine is lightweight enough for hand-held outdoor power equipment—and clean enough for stringent emissions standards that are coming soon.



WHAT'S NEW..... 12

SCIENCE AND TECHNOLOGY

Science newsfront	3
Buried sunshine heats sports center	21
Out of the black:	J
secret Mach 6 spy plane	5
The unbearable lightness of space travel	7
Mr. Babbage's wonderful calculating machine	
calculating machine	OI

COMPUTERS AND ELECTRONICS

CARS AND DRIVING

Automotive newsfront	46
Car test: minivans to the max	80

HOME PRODUCTS AND TECHNOLOGY

Home newsfront	39
New American Home 1993:	
a house for all reasons	66
The little engine that could	90

ADDITIONAL FEATURES

From the editor	4
Readers talk back	
Product information	
Looking back	

COVER ILLUSTRATION BY KERRY LESLIE

Reprinted from POPULAR SCIENCE with permission © 1993 by Tirnes Mirror Magazines, Inc.

This four-cycle engine is lightweight enough:

for hand-held equipment and dean


emowalk for Callifornia

BY JUDITH ANNE GUNTHER

fere claimed experts in the orifdour power tool industry, was a problem without: Tready solution. How could she y build grandy solution with the solution of the sufficiently clean burning to meet increasingly demanding legislation?

Now one manufacturer, Ryobi North America, the South Carolina based subsidiary of the Japanese toolomaker, says it has an answer, Ryobis GleanAir engine is a radically scaled-down 26cc four cycle engine that defly delivers one horsepower in an eight-pound package. And Ryobi is betting that this engine will heavily influence the hand held outdoor power tools that consumers buy in the mid-1990s.

For decades, manufacturers have relied on two-cycle engine to power chain saws, trimmers, blowers and sother tools that require light weight and bruit force taking salvantage of a power pulse with every crankshaft evolution of Greener Pastures, July-921-But such performance that step process are pollution—and in 1990 the control of the state of the process of



says Ryobi senior vice president William McLay. "First, it had to meet California's emissions standards. Second, it could not be any heavier than current two-cycle engines. Third, it couldn't cost significantly more than high-end engines. And we feel that the CleanAir engine meets these parameters."

In theory, building a small four-cycle engine might not seem difficult, but in reality Ryobi faced numerous design and manufacturing hurdles. Today's small four-cycle engines normally weigh 40 pounds and generate about 3.5 horsepower. The CleanAir engine, in comparison, weighs just eight pounds and generates one horsepower. Such dramatic downsizing required smaller components; some parts, such as the valves, didn't exist and had to be designed and manufactured specifically for this engine.

Still, industry experts are cautious when discussing the engine. "There's no magic here," remarks Glenn Keller of the Engine Manufacturers Association in Chicago. While he acknowledges the difficulties in design, he sums that "Ryobi has just miniaturized everything."

A logical analysis in the broad sense, but, as additional research indicates, something of an underestimate of the cleverness of the Ryobi engine design. Such a simplistic engine-shrinking could certainly have produced the low

emissions levels and perhaps the necessary power output, but doubtfully could have done it at a competitive manufacturing cost. Here the Clean-Air engine demonstrates some unique design solutions that give it a clear edge, at least for the time being.

"We are aware—at least it's rumored in the industry—that other manufacturers have made small four-cycle engines," McLay says. "But they're either polluting or very costly or too heavy." Likewise, tiny four-cycle engines used in another application—model airplanes—don't fit the bill for running trimmers and blowers. "That's a whole different power class," says McLay.

o operate a grass trimmer, he explains, a small four-cycle engine must turn at about 7,000 or 8,000 rpm—twice the speed of a mower-type engine. Increasing speed means increased heat, and possibly increased wear on engine parts. Although McLay won't reveal the metallurgy processes that were employed ("We hope it will take a while for our competitors to figure it out," he says), he does allude to alloys, heat-treating methods, and materials chosen for their lubricity.

To keep engine temperatures down, Ryobi engineers worked out an unusual two-piece cylinder head consisting of a lower casting that houses the combustion chamber and an upper section that encloses the rocker arms used to open the valves. This design permits cooling fins to be placed strategically next to some of the hottest areas of the engine—the exhaust valve and bridge area between the valves.


For all of the development effort Ryobi invested in it, the CleanAir engine must still be competitive with other products if it is to sell in the 49 states that don't have emissions regulations yet. (The EPA is reviewing emissions data of so-called utility engines; nationwide regulations may be announced by the end of 1993.)

"Only certain people will buy a product because it is environmentally friendly," McLay acknowledges. Performance, he maintains, will be a major selling point.

The most significant benefit consumers will find is the more consistent power produced by four-strokes. "The characteristic of a two-cycle engine is that it has to be very high on the rpm curve to get the most torque output," he explains. "But a four-cycle has a flatter curve, so when the engine is working hard, it still produces the torque. As rpm drops, torque doesn't drop much at all."

Another plus inherent in a four-cycle engine is that it doesn't require a gasoil mixture. Instead, lubricant is distributed by a dipper at the end of the connecting rod—the conventional

(Continued on page 96)



The little engine that could

[Continued from page 92]

splash-type system used in small fourcycles—which Ryobi claims will be effective even with the engine running inverted. By itself, it would seem unlikely that the dipper system could possibly live up to that assertion. That is, until you learn that both ends of the connecting rod ride on caged roller bearings (rather than conventional insert shells), which get along fine on very small amounts of oil. As a side benefit, the weight, cost, and power

drain of an oil-circulating pump have been eliminated.

The caged roller bearings are fitted into a steel connecting rod that is built up from two separate stampings, rather than the usual casting or forging. The stamped parts are left and right sections; there is no separate bearing cap at the bottom end. This construction technique requires that the crankshaft be pressed together from individual pieces for ease of as-

sembly, and here again Ryobi breaks from tradition by using a stamped counterweight section mated to a simple steel output shaft. Additionally, overall engine weight is kept low by the crankshaft's cantilevered design; the engine is supported in ball bearings only on the flywheel side, ending abruptly at the connecting rod.

The enlightened engineering doesn't end there, either. To eliminate a heavy iron cylinder sleeve, the CleanAir engine is built with a long-lasting, flash-chromed aluminum cylinder bore. The valve train operates from one cam lobe, using an ingenious follower mechanism that simultaneously converts the cam's rotation to the required reciprocating motion and also turns the action 90 degrees to line up with the ball-pivot rocker arms.

In addition to exhaust emissions, Ryobi addressed another form of pollution: noise. While the CleanAir engine's noise level is only a few decibels less than most engines, the biggest difference is its deeper pitch. "The improvement is the quality of the sound," says McLay. "High-pitched sounds and lower-pitched sounds at the same decibel level are two different experiences to the human ear."

Computer-aided-design technology played a major role in this process. "We incorporated a large-volume muffler, but what's more, we used computer-aided design to create noise-canceling baffling," he says. To reduce the noise generated by the gear drive, engineers designed gear profiles that would operate more quietly and then manufactured the gears in a powdered-metal material that provides some advantage in sound damping.

Now engineers are ironing out the last details, including smoothing the engine's vibrations. "We're still finetuning that," says McLay. "Four-cycle engines tend to vibrate more than two-cycles because they fire every other stroke."

A 1994 debut

The CleanAir engine will be manufactured almost entirely in Arizona and will first appear in a hand-held grass trimmer at the industry's exposition this summer in Louisville, Ky. Consumers can expect to see that product on store shelves in the first part of 1994. Meanwhile, McLay says Ryobi will consider applying the technology to other outdoor power tool products, such as brush cutters, cultivators, and leaf blowers, as well as licensing the engine to manufacturers of water pumps, mowers, and highpower washers.



Making Innovative Concepts A Reality $^{\mathsf{m}}$

Ryobi America Corp. P.O. Box 1207 Anderson, SC 29622-1207 803-226-6511

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER: ____

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.